

TUYAU GAS OIL EN/ISO 6806

Tube intérieur: NBR

Recouvrement: 1 Tresse acier Galvanisé -

Température d'utilisation de -30°C à +90°C

Code	Désignation	Diam Int.		Mod	Ø EXT	Max PS	PLNE	Min RC	Poids Kg/m	Jupe Préconisée
		in	mm							
0246059500	GTG05	3/16"	0.0	03	9.0	20	175	32		JUPE G 05
0246069501	GTG06	1/4"	0.0	04	10.0	20	160	40		JUPE G 06
0246089502	GTG08	5/16"	0.0	05	12.0	20	150	48		JUPE G 08
0246109503	GTG10	3/8"	0.0	06	14.0	16	115	60		JUPE G 10
0246129504	GTG12	1/2"	0.0	08	18.0	16	95	72		JUPE G 12
0246159505	GTG15	5/8"	0.0	10	22.0	16	70	88		JUPE G 15
0246199506	GTG17	3/4"	0.0	12	28.0	10	50	112		JUPE G 17
0246229507	GTG22	1"	0.0	16	3.0	6	40	140		JUPE G 22



Tuyau armé tresse textile extérieur vulcanisé DIN73379B

Tube intérieur: NBR

Recouvrement: 1 Tresse textile imprégnée -

Température d'utilisation de -40°C à +125°C (140°C en pointe)

Code	Désignation	Diam Int.		Mod	Ø EXT	Max PS	PLNE	Min RC	Poids Kg/m	Jupe Préconisée
		in	mm							
0246039520	GTTO3 (OLN03)		3.0	02	10.0	75		30		JUPE G 04
0246059501	GTT05 (OLN05)		5.0	03	11.0	70		35		JUPE G 05
0246069509	GTT06 (OLN06)		6.0	04	12.0	65		40		JUPE G 06
0246089510	GTT08 (OLN08)		8.0	05	14.0	55		50		JUPE G 08
0246109504	GTT10 (OLN10)		10.0	06	15.0	50		55		JUPE G 10
0246129505	GTT12 (OLN12)		12.0	08	19.0	50		70		JUPE G 12

